

TECHNICAL DATA SHEET

www.regalfloorpaint.co.uk

2-Pack Epoxy Floor Paint (Top Coat)

Product Description & Recommended Use

- Economical long-term protection in demanding conditions.
- Incredibly durable and hard-wearing with excellent resistance to water, solvents, acids, alkalis and salts.
- Excellent cross-linking with Regal 2-Pack Epoxy Floor Sealer (First Coat).
- Trouble-free application by roller or brush.
- Recommended for heavy-duty commercial and industrial areas.
- Ideal for areas that will be receiving heavy traffic such as vehicles and trucks.

Designed for application to concrete and non ferrous metals, Regal 2-Pack Epoxy Floor Paint (Top Coat) is the second coat in the Regal 2-Pack Epoxy Flooring System.

Regal 2-Pack Epoxy Floor Paint (Top Coat) is incredibly durable and hard-wearing, making it ideal for use on areas that will be receiving heavy traffic, such as vehicles and trucks. It gives excellent protection against water, solvents, acids, alkalis and salts.

A tough finish and long-lasting abrasion and impact resistance.

Resistance Guide		
Environment	Splash and Spillage	Fumes and Weathering
Acid	Fair	Good
Alkaline	Excellent	Excellent
Salt Solution (Acidic)	Excellent	Very Good
Salt Solution (Neutral)	Excellent	Excellent
Salt Solution (Alkaline)	Excellent	Excellent
Water	Excellent	Excellent

Typical Uses	
Warehouse Flooring	Manufacturing Plants
Factory Flooring	Engineering Works
Chemical Plants	Automotive Garages
Refineries	Showroom Flooring
Offshore Platforms	Breweries
Pulp and Paper Mills	Kennels & Catteries
And other flooring applications requiring durability and chemical protection	

Key Benefits

- Incredibly Durable and Hardwearing
- Heavy Duty
- Cross-Links with Regal 2-Pack Epoxy Floor Sealer (First Coat)

Complies with all current legislation at the time of writing.

TECHNICAL DATA SHEET 2-Pack Epoxy Floor Sealer (First Coat)

Standard Colours	Slate Grey, Light Grey, Brunswick Green, Ford Tractor Blue, Cornflower Blue, Red Oxide, Post Office Red, Caterpillar Yellow, JCB Yellow, Chocolate Brown, Bright Orange, Black, White. Other RAL and British Standard colours can be made, dependent on the quantities required.
Dry Film Appearance	Sheen
Substrates	Concrete and non-ferrous metals
Components	2 (Resin and Hardener/Activator)
Curing Mechanism	Solvent release and chemical reaction between components
Mixing Ratio (by Volume)	Resin 4 parts: Hardener/Activator 1 part
Induction Time	10 minutes (at 20°C)
Pot Life	3 hours at 20°C (pot life is dependent on temperature and quantities mixed)
Spreading Rate	5-7m ² per litre at 125µm (allow for application losses, surface irregularities etc.)
Touch Dry @20°C	12-16 hours
Recoating Time @20°C	24 hours
Hard-Drying Time	48 hours
Full Cure	7 days
Typical Wet-Film Thickness	230µm per coat
Typical Dry-Film Thickness	150µm per coat
Solids by Volume	63% (ASTM D2697) ±3%, dependent on colour
VOC Information	22% by weight (190g/kg)
Specific Gravity	1.68 kg per litre (mixed product)
Application Temperature	Minimum 5
Application Method	Roller or brush
Thinners	Standard Thinner
Flash Point	Resin 36°C; Hardener/Activator 33°C (Closed Cup)
Pack Size	5 litres (Resin 4 litres: Hardener/Activator 1 litre); 20 litres (Resin 16 litres: Hardener/Activator 4 litres)
Shelf Life	12 months (when stored indoors, unopened, in the original containers at 5-30°C)

Recommendations following application of this product

- Do not park vehicles or place heavy machinery/equipment onto the floor for a minimum of 48 hours.
- Following application, do not get the floor wet for a minimum of 7 days as this will cause bloom (discolouration).

Complies with all current legislation at the time of writing.