

PRODUCT DATA SHEET

www.regalfloorpaint.co.uk

Line-Marking Paint

Product Description & Recommended Use

- A single-pack, quick-drying, high-build line-marking paint providing good durability and impact resistance.
- A bright, hard-wearing paint ideal for the demarcation of hazard zones, footways, loading bays etc.
- Moderate protection against solvents, salt, water and cleaning chemicals.
- Suitable for medium-duty commercial and industrial areas.
- Easy to apply by roller and brush and easy to repaint on high-wear areas.

Standard Colours	Post Office Red, JCB Yellow, Bright Orange, Black, White. Other RAL and British Standard colours can be made, dependent on the quantities required.
Dry Film Appearance	Semi-gloss
Spreading Rate	5-8m ² per litre, dependent on film thickness (10m ² @ 50µm; 5m ² @ 100µ)
Touch Dry @20°C	3-4 hours
Recoating Time @20°C	Minimum 24 hours
Typical Wet-Film Thickness	85-135µm per coat
Typical Dry-Film Thickness	50-100µm per coat
Solids by Volume	58% (ASTM D2697) ±3%, dependent on colour
VOC Information	420g per litre (from formula to satisfy EU Solvent Emissions Directive)
Application Temperature	10-35°C
Application Method	Brush or roller
Substrates	Suitably cleaned and dry surfaces
Thinners	Thinning not recommended. For cleaning, use standard thinners.
Flash Point	>25°C
Pack Size	5 litre can; 20 litre can; 205 litre barrel
Shelf Life	12 months

Key Benefits

- High Performance
- Quick Dry
- Formulated with High Quality Synthetic Resins

Complies with all current legislation at the time of writing.